

HALOSOL S

Version Revision Date: SDS Number: Date of last issue: 21.05.2022 1.1 03.01.2023 100000021603 Date of first issue: 21.05.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name HALOSOL S

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-

stance/Mixture

: Adhesive

Recommended restrictions

on use

For industrial use only.

1.3 Details of the supplier of the safety data sheet

: H.B. Fuller, Isar-Rakoll, S.A. Company

Address Estrada Nacional 13

PT-4486-851 Mindelo - Vila do Conde

+351 229 288 200

E-mail address of person

responsible for the SDS

EU-MSDS@hbfuller.com

1.4 Emergency telephone number

Emergency telephone number : +44 1235 239 670 (24 hours)

National Poisons Information Centre (NPIC): 01 809 2566 (24

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2 H225: Highly flammable liquid and vapour.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Specific target organ toxicity - single exposure, Category 3, Central nervous

system

H336: May cause drowsiness or dizziness.

Long-term (chronic) aquatic hazard, Cat-

egory 3

H412: Harmful to aquatic life with long lasting ef-

fects.

HALOSOL S

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.05.2022

 1.1
 03.01.2023
 100000021603
 Date of first issue: 21.05.2022

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms

Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

Supplemental Hazard

Statements

EUH031

Contact with acids liberates toxic gas.

EUH066 Repeated exposure may cause skin

dryness or cracking.

Precautionary statements : Prevention:

P210 Keep away from heat, hot surfaces, sparks, open

flames and other ignition sources. No smoking.

P233 Keep container tightly closed.P261 Avoid breathing mist or vapours.P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protec-

tion/ face protection/ hearing protection.

Response:

P370 + P378 In case of fire: Use dry sand, dry chemical or

alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

ethyl acetate

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Index-No.		



HALOSOL S

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.05.2022

 1.1
 03.01.2023
 100000021603
 Date of first issue: 21.05.2022

	Registration number		
ethyl acetate	141-78-6 205-500-4 607-022-00-5 01-2119475103-46- 0000	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system) EUH066	>= 90 - <= 100
symclosene	87-90-1 201-782-8 613-031-00-5 01-2120767978-27- 0000	Ox. Sol. 2; H272 Acute Tox. 4; H302 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH031 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	>= 1 - < 2,5
		Acute toxicity estimate Acute oral toxicity: 406 mg/kg	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : If on clothes, remove clothes.

Move the victim to fresh air.

Show this safety data sheet to the doctor in attendance. Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the

accident.

If inhaled : Remove person to fresh air. If signs/symptoms continue, get

medical attention.

In case of unconsciousness bring patient into stable side posi-

tion for transport.

In case of skin contact : Wash off immediately with soap and plenty of water while

HALOSOL S

Version Revision Date: SDS Number: Date of last issue: 21.05.2022 100000021603 1.1 03.01.2023 Date of first issue: 21.05.2022

> removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

In case of eye contact Flush eyes with water at least 15 minutes. Get medical atten-

tion if eye irritation develops or persists.

If swallowed If accidentally swallowed obtain immediate medical attention.

Rinse mouth with water.

If conscious, drink plenty of water.

Do NOT induce vomiting.

If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Water mist Foam Dry powder

Carbon dioxide (CO2)

Unsuitable extinguishing

media

: Water with a full water jet

5.2 Special hazards arising from the substance or mixture

fighting

Specific hazards during fire- : No further relevant information available.

5.3 Advice for firefighters

for firefighters

Special protective equipment : No special protective measures against fire required.

Further information In the event of fire, wear self-contained breathing apparatus.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.



HALOSOL S

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.05.2022

 1.1
 03.01.2023
 100000021603
 Date of first issue: 21.05.2022

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Remove all sources of ignition.

Use personal protective equipment.

Use breathing protection against the effects of

fumes/dust/aerosol.

Evacuate personnel to safe areas. Ensure adequate ventilation.

6.2 Environmental precautions

Environmental precautions : The product should not be allowed to enter drains, water

courses or the soil.

Prevent the material from reaching sewage system, holes and

cellars.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust). Non-sparking tools should be used.

Ensure adequate ventilation.

Send for recovery or disposal in suitable containers.

Dispose of contaminated material as waste according to sec-

tion 13.

6.4 Reference to other sections

Refer to protective measures listed in sections 7 and 8., For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of dust and aerosols.

Use only with adequate ventilation. Take note of emission threshold. Use solvent-proof equipment.

Ensure that suitable extractors are available on processing

machines. Handle with care.

Keep eye wash bottle available on working place.

Avoid release to the environment.

Keep away from children.

Advice on protection against

fire and explosion

Keep product and empty container away from heat and sources of ignition. Do not smoke. Take measures to prevent the build up of electrostatic charge. May form explosive mix-

HALOSOL S

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.05.2022

 1.1
 03.01.2023
 100000021603
 Date of first issue: 21.05.2022

tures in air. Highly volatile, flammable constituents are released during processing. In the event of fire and/or explosion do not breathe fumes. Keep breathing equipment ready. Have fire extinguishing equipment ready in case of nearby fire.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Keep dark, cool and dry. Store in cool place.

Further information on stor-

age conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Store in a cool place. Heat will increase

pressure and may lead to the container exploding.

7.3 Specific end use(s)

Specific use(s) : No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis	
ethyl acetate	141-78-6	OELV - 8 hrs	200 ppm	IE OEL	
		(TWA)	734 mg/m3		
		OELV - 15 min	400 ppm	IE OEL	
		(STEL)	1.468 mg/m3		
		STEL	400 ppm	2017/164/EU	
			1.468 mg/m3		
	Further information: Indicative				
		TWA	200 ppm	2017/164/EU	
			734 mg/m3		
	Further information: Indicative				

8.2 Exposure controls

Engineering measures

Please take care on national and local requirements.

Personal protective equipment

Eye protection : Tightly fitting safety goggles

Hand protection

HALOSOL S

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.05.2022

 1.1
 03.01.2023
 100000021603
 Date of first issue: 21.05.2022

Remarks

: The glove material has to be impermeable and resistant to the product/the substance/the preparation.

The exact break through time can be obtained from the protective glove producer and this has to be observed.

The gloves need to be disposed after the penetration time

and replaced by new ones.

Apply skin protectant before working with gloves to avoid skin swellings and use a skin cleansing and skincare product after the work.

For the permanent contact gloves made of the following materials are suitable:

If longer exposure to the chemical preparation is necessary, a sturdy overglove against mechanical strain is recommended in combination with the Barrier 02-100 underglove from Ansell or other suppliers (penetration time: 480 min).

For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable: Butyl rubber (minimum thickness: 0.7 mm; penetration time: 15 min)

As protection from splashes gloves made of the following materials are suitable:

Nitril (minimum thickness 0.12 mm), Disposable gloves with long cuffs

After contact with the chemical preparation, take the disposable nitrile glove off immediately and put on a new disposable nitrile glove.

Skin and body protection : Protective clothing

Respiratory protection : Use respiratory protection unless adequate local exhaust ven-

tilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. In case of brief exposure or low pollution (exceeding of TLV)

use breathing filter apparatus.

In case of intensive or longer exposure use breathing appa-

ratus that is independent of circulating air.

Ensure that suitable extractors are available on processing

machines.

Protective measures : Keep away from food, drink and animal feedingstuffs.

Instantly remove any soiled and impregnated garments. Wash hands before breaks and immediately after handling

the product.

Avoid contact with the eyes and skin. Store protective clothing separately.

HALOSOL S

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.05.2022

 1.1
 03.01.2023
 100000021603
 Date of first issue: 21.05.2022

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid

Colour : yellow

Odour : pungent

Odour Threshold : is not determined

Melting point/freezing point : is not determined

Boiling point/boiling range : 76 °C

Flash point : -4 °C

Auto-ignition temperature : is not determined

Decomposition temperature : Not applicable

pH : substance/mixture is non-polar/aprotic

Solubility(ies)

Water solubility : not miscible or difficult to mix

Partition coefficient: n-

octanol/water

no data available

Vapour pressure : 97 hPa (20 °C)

Density : 0,9000 g/cm³

Relative vapour density : is not determined

9.2 Other information

Explosives : Product is not explosive. However, formation of explosive

vapour/air mixtures is possible.

Evaporation rate : is not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

No further relevant information available.



HALOSOL S

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.05.2022

 1.1
 03.01.2023
 100000021603
 Date of first issue: 21.05.2022

10.2 Chemical stability

No decomposition if used according to the specifications.

10.3 Possibility of hazardous reactions

Hazardous reactions : Develops readily flammable vapours/fumes.

10.4 Conditions to avoid

Conditions to avoid : No further relevant information available.

10.5 Incompatible materials

Materials to avoid : No further relevant information available.

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product:

Acute oral toxicity : Based on available data, the classification criteria are not met.

Acute toxicity estimate: > 2.000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Based on available data, the classification criteria are not met.

Acute dermal toxicity : Based on available data, the classification criteria are not met.

Components:

ethyl acetate:

Acute oral toxicity : LD50 Oral (Rat): 5.620 mg/kg

Acute inhalation toxicity : LC50 (Rat): 22,5 mg/l

Exposure time: 4 h

Acute dermal toxicity : LD50 Dermal (Rabbit): > 20.000 mg/kg

symclosene:

Acute oral toxicity : LD50 Oral (Rat): 406 mg/kg

Acute toxicity estimate: 406 mg/kg Method: Calculation method

HALOSOL S

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.05.2022

 1.1
 03.01.2023
 100000021603
 Date of first issue: 21.05.2022

Acute inhalation toxicity : LC50 (Rat): > 50 mg/l

Exposure time: 1 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2.000 mg/kg

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

ethyl acetate:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 220 - 250

mg/l

Exposure time: 96 h

Test Type: flow-through test

symclosene:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 0,06 - 0,11 mg/l

Exposure time: 96 h Test Type: static test

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 0,16 - 0,18 mg/l

Exposure time: 48 h Test Type: static test

M-Factor (Acute aquatic tox- :

icity)

: 1

M-Factor (Chronic aquatic

toxicity)

: 1

12.2 Persistence and degradability

No data available

HALOSOL S

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.05.2022

 1.1
 03.01.2023
 100000021603
 Date of first issue: 21.05.2022

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

Product:

Mobility : Medium: Soil

Remarks: Do not allow product to reach ground water, water

bodies or sewage system.

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of with domestic refuse.

Do not dispose of waste into sewer.

Hand over to disposers of hazardous waste.

The generation of waste should be avoided or minimized

wherever possible.

Incinerate under controlled conditions in accordance with all

local and national laws and regulations.

Disposal must be made according to official regulations.

These EU waste code numbers are recommendations for waste accruing through the use of adhesives and sealants. Any waste produced from organic solvents or other dangerous substances (according GHS) listed under section 3 of this safety datasheet is itself classified as dangerous (*).

Waste accruing during application:

HALOSOL S

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.05.2022

 1.1
 03.01.2023
 100000021603
 Date of first issue: 21.05.2022

08 04 09* waste adhesives and sealants containing or-

ganic solvents or other dangerous substances

08 04 10 waste adhesives and sealants other than

those mentioned in 08 04 09

Waste accruing during cleaning:

08 04 11* adhesive and sealant sludges containing or-

ganic solvents or other dangerous substances

08 04 12 adhesive and sealant sludges other than

those mentioned in 08 04 11

Waste packaging:

15 01 01 paper and cardboard packaging

15 01 02 plastic packaging 15 01 04 metallic packaging

15 01 10* packaging containing residues of or contami-

nated by dangerous substances.

Contaminated packaging : Disposal must be made according to official regulations.

SECTION 14: Transport information

14.1 UN number or ID number

ADR : UN 1173
RID : UN 1173
IMDG : UN 1173
IATA : UN 1173

14.2 UN proper shipping name

ADR : ETHYL ACETATE
RID : ETHYL ACETATE
IMDG : ETHYL ACETATE

IATA : Ethyl acetate

14.3 Transport hazard class(es)

 ADR
 : 3

 RID
 : 3

 IMDG
 : 3

 IATA
 : 3

14.4 Packing group

ADR

Packing group : II

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HALOSOL S

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.05.2022

 1.1
 03.01.2023
 100000021603
 Date of first issue: 21.05.2022

Classification Code : F1
Hazard Identification Number : 33
Labels : 3
Tunnel restriction code : (D/E)

RID

Packing group : II
Classification Code : F1
Hazard Identification Number : 33
Labels : 3

IMDG

Packing group : II
Labels : 3
EmS Code : F-E, S-D

IATA (Cargo)

Packing instruction (cargo : 364

aircraft)

Packing instruction (LQ) : Y341
Packing group : II

Labels : Flammable Liquids

IATA_P (Passenger)

Packing instruction (passen: 353

ger aircraft)

Packing instruction (LQ) : Y341
Packing group : II

Labels : Flammable Liquids

14.5 Environmental hazards

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture



HALOSOL S

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.05.2022

 1.1
 03.01.2023
 100000021603
 Date of first issue: 21.05.2022

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances.

mixtures and articles (Annex XVII)

: Conditions of restriction for the following entries should be considered:

Number on list 3

acetic acid

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

Not applicable

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Not applicable

RoHS: 2011/65/EU, Restriction of Hazardous Substanc-

es

Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import

of dangerous chemicals

Not applicable

REACH - List of substances subject to authorisation

(Annex XIV)

Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous

substances.

FLAMMABLE LIQUIDS

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial

P5c

emissions (integrated pollution prevention and control)

Volatile organic compounds (VOC) content: 97,85 %, 880,7 g/l

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

The components of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

AIIC : On the inventory, or in compliance with the inventory

REACH : On the inventory, or in compliance with the inventory

HALOSOL S

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.05.2022

 1.1
 03.01.2023
 100000021603
 Date of first issue: 21.05.2022

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture.

SECTION 16: Other information

Full text of H-Statements

H225 : Highly flammable liquid and vapour.

H272 : May intensify fire; oxidizer. H302 : Harmful if swallowed.

H319 : Causes serious eye irritation.
H335 : May cause respiratory irritation.
H336 : May cause drowsiness or dizziness.

H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.

EUH031 : Contact with acids liberates toxic gas.

EUH066 : Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Acute : Short-term (acute) aquatic hazard
Aquatic Chronic : Long-term (chronic) aquatic hazard

Eye Irrit. : Eye irritation
Flam. Liq. : Flammable liquids
Ox. Sol. : Oxidizing solids

STOT SE : Specific target organ toxicity - single exposure

2017/164/EU : Europe. Commission Directive 2017/164/EU establishing a

fourth list of indicative occupational exposure limit values

IE OEL : Ireland. List of Chemical Agents and Occupational Exposure

Limit Values - Schedule 1

2017/164/EU / STEL : Short term exposure limit 2017/164/EU / TWA : Limit Value - eight hours

IE OEL / OELV - 8 hrs (TWA) : Occupational exposure limit value (8-hour reference period)
IE OEL / OELV - 15 min : Occupational exposure limit value (15-minute reference peri-

(STEL) od)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL

HALOSOL S

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.05.2022

 1.1
 03.01.2023
 100000021603
 Date of first issue: 21.05.2022

- Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI -Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information : This safety datasheet only contains information relating to

safety and does not replace any product information or prod-

uct specification.

Contact Point : Prepared by: Global Regulatory Department

EU-MSDS@hbfuller.com

Classification of the mixture: Classification procedure:

Flam. Liq. 2 H225 Based on product data or assessment

Eye Irrit. 2 H319 Calculation method STOT SE 3 H336 Calculation method Aquatic Chronic 3 H412 Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

IE / EN