

**SAFETY DATA SHEET**

according to Regulation (EC) No. 1907/2006

**Köraplast® SF**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	24.08.2022	100000017516	Date of first issue: 24.08.2022

---

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier****Product name** : Köraplast® SF**1.2 Relevant identified uses of the substance or mixture and uses advised against**Use of the Sub-  
stance/Mixture : AdhesiveRecommended restrictions  
on use : For industrial use only.**1.3 Details of the supplier of the safety data sheet**

Company : H.B. Fuller, Isar-Rakoll, S.A.

Address : Estrada Nacional 13  
PT-4486-851 Mindelo - Vila do Conde  
+351 229 288 200E-mail address of person  
responsible for the SDS : EU-MSDS@hbfuller.com**1.4 Emergency telephone number**

Emergency telephone number : +44 1235 239 670 (24 hours)

National Poisons Information Centre (NPIC): 01 809 2566 (24 hours)

---

**SECTION 2: Hazards identification****2.1 Classification of the substance or mixture****Classification (REGULATION (EC) No 1272/2008)**

Flammable liquids, Category 2 H225: Highly flammable liquid and vapour.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Specific target organ toxicity - single exposure, Category 3, Central nervous system H336: May cause drowsiness or dizziness.

Long-term (chronic) aquatic hazard, Category 3 H412: Harmful to aquatic life with long lasting effects.

**SAFETY DATA SHEET**

according to Regulation (EC) No. 1907/2006

**Köraplast® SF**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	24.08.2022	100000017516	Date of first issue: 24.08.2022

**2.2 Label elements****Labelling (REGULATION (EC) No 1272/2008)**

Hazard pictograms :



Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 Keep container tightly closed.  
P261 Avoid breathing mist or vapours.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

**Response:**

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

**Hazardous components which must be listed on the label:**

acetone  
ethyl acetate  
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane  
butanone

**2.3 Other hazards**

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

**SECTION 3: Composition/information on ingredients****3.2 Mixtures****Components**

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
acetone	67-64-1	Flam. Liq. 2; H225	>= 50 - < 70

**SAFETY DATA SHEET**

according to Regulation (EC) No. 1907/2006

**Körplast® SF**

Version 1.0	Revision Date: 24.08.2022	SDS Number: 100000017516	Date of last issue: - Date of first issue: 24.08.2022
----------------	------------------------------	-----------------------------	--

	200-662-2 606-001-00-8 01-2119471330-49-0000	Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system) EUH066	
ethyl acetate	141-78-6 205-500-4 607-022-00-5 01-2119475103-46-0000	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system) EUH066	$\geq 1 - < 10$
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	64742-49-0 921-024-6 01-2119475514-35-0000	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Aquatic Chronic 2; H411 Skin Irrit. 2; H315 STOT SE 3; H336 (Respiratory system)	$\geq 2,5 - < 10$
butanone	78-93-3 201-159-0 606-002-00-3 01-2119457290-43-0000	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system) EUH066	$\geq 1 - < 10$
n-hexane	110-54-3 203-777-6 601-037-00-0 01-2119480412-44-0000	Flam. Liq. 2; H225 Skin Irrit. 2; H315 Repr. 2; H361f STOT SE 3; H336 (Central nervous system) STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Chronic 2; H411  specific concentration limit STOT RE 2; H373 $\geq 5 \%$	$\geq 0,1 - < 0,25$

For explanation of abbreviations see section 16.

**SECTION 4: First aid measures**
**4.1 Description of first aid measures**

General advice : If on clothes, remove clothes.

**SAFETY DATA SHEET**

according to Regulation (EC) No. 1907/2006

**Köraplast® SF**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	24.08.2022	100000017516	Date of first issue: 24.08.2022

Move the victim to fresh air.  
Show this safety data sheet to the doctor in attendance.  
Symptoms of poisoning may even occur after several hours;  
therefore medical observation for at least 48 hours after the  
accident.

- |                         |   |   |
|-------------------------|---|---|
| If inhaled              | : | Remove person to fresh air. If signs/symptoms continue, get medical attention.<br>In case of unconsciousness bring patient into stable side position for transport.                                   |
| In case of skin contact | : | Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.<br>If skin irritation persists, call a physician.   |
| In case of eye contact  | : | Flush eyes with water at least 15 minutes. Get medical attention if eye irritation develops or persists.  |
| If swallowed            | : | If accidentally swallowed obtain immediate medical attention.<br>Rinse mouth with water.<br>If conscious, drink plenty of water.<br>Do NOT induce vomiting.<br>If symptoms persist, call a physician. |

**4.2 Most important symptoms and effects, both acute and delayed**

None known.

**4.3 Indication of any immediate medical attention and special treatment needed**

Treatment : No further relevant information available.

---

**SECTION 5: Firefighting measures****5.1 Extinguishing media**

Suitable extinguishing media	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Water mist Foam Dry powder Carbon dioxide (CO <sub>2</sub> )
------------------------------	---	--

Unsuitable extinguishing media	:	Water with a full water jet
--------------------------------	---	-----------------------------

**5.2 Special hazards arising from the substance or mixture**

Specific hazards during fire-fighting	:	No further relevant information available.
---------------------------------------	---	--

**SAFETY DATA SHEET**

according to Regulation (EC) No. 1907/2006

**Köraplast® SF**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	24.08.2022	100000017516	Date of first issue: 24.08.2022

---

**5.3 Advice for firefighters**

Special protective equipment : No special protective measures against fire required.  
for firefighters

Further information : In the event of fire, wear self-contained breathing apparatus.  
Fire residues and contaminated fire extinguishing water must  
be disposed of in accordance with local regulations.  
Collect contaminated fire extinguishing water separately. This  
must not be discharged into drains.

---

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**

Personal precautions : Remove all sources of ignition.  
Use personal protective equipment.  
Use breathing protection against the effects of  
fumes/dust/aerosol.  
Evacuate personnel to safe areas.  
Ensure adequate ventilation.

**6.2 Environmental precautions**

Environmental precautions : The product should not be allowed to enter drains, water  
courses or the soil.  
Prevent the material from reaching sewage system, holes and  
cellars.  
If the product contaminates rivers and lakes or drains inform  
respective authorities.

**6.3 Methods and material for containment and cleaning up**

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,  
acid binder, universal binder, sawdust).  
Non-sparking tools should be used.  
Ensure adequate ventilation.  
Send for recovery or disposal in suitable containers.  
Dispose of contaminated material as waste according to sec-  
tion 13.

**6.4 Reference to other sections**

Refer to protective measures listed in sections 7 and 8., For disposal considerations see section 13.

---

**SECTION 7: Handling and storage****7.1 Precautions for safe handling**

Advice on safe handling : Avoid formation of dust and aerosols.  
Use only with adequate ventilation.  
Take note of emission threshold.

**SAFETY DATA SHEET**

according to Regulation (EC) No. 1907/2006

**Köraplast® SF**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	24.08.2022	100000017516	Date of first issue: 24.08.2022

Use solvent-proof equipment.  
Ensure that suitable extractors are available on processing machines.  
Handle with care.  
Keep eye wash bottle available on working place.  
Avoid release to the environment.  
Keep away from children.

Advice on protection against fire and explosion : Keep product and empty container away from heat and sources of ignition. Do not smoke. Take measures to prevent the build up of electrostatic charge. May form explosive mixtures in air. Highly volatile, flammable constituents are released during processing. In the event of fire and/or explosion do not breathe fumes. Keep breathing equipment ready. Have fire extinguishing equipment ready in case of nearby fire.

**7.2 Conditions for safe storage, including any incompatibilities**

Requirements for storage areas and containers : Keep dark, cool and dry. Store in cool place.

Further information on storage conditions : Keep containers tightly closed in a dry, cool and well-ventilated place. Store in a cool place. Heat will increase pressure and may lead to the container exploding.

**7.3 Specific end use(s)**

Specific use(s) : No further relevant information available.

**SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
acetone	67-64-1	TWA	500 ppm 1.210 mg/m <sup>3</sup>	2000/39/EC
Further information: Indicative				
		OELV - 8 hrs (TWA)	500 ppm 1.210 mg/m <sup>3</sup>	IE OEL
ethyl acetate	141-78-6	OELV - 8 hrs (TWA)	200 ppm 734 mg/m <sup>3</sup>	IE OEL
		OELV - 15 min (STEL)	400 ppm 1.468 mg/m <sup>3</sup>	IE OEL
		STEL	400 ppm 1.468 mg/m <sup>3</sup>	2017/164/EU
Further information: Indicative				
		TWA	200 ppm	2017/164/EU

**SAFETY DATA SHEET**

according to Regulation (EC) No. 1907/2006

**Körplast® SF**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	24.08.2022	100000017516	Date of first issue: 24.08.2022

			734 mg/m3	
	Further information: Indicative			
butanone	78-93-3	STEL	300 ppm 900 mg/m3	2000/39/EC
	Further information: Indicative			
		TWA	200 ppm 600 mg/m3	2000/39/EC
	Further information: Indicative			
		OELV - 8 hrs (TWA)	200 ppm 600 mg/m3	IE OEL
	Further information: Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body			
		OELV - 15 min (STEL)	300 ppm 900 mg/m3	IE OEL
	Further information: Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body			
n-hexane	110-54-3	TWA	20 ppm 72 mg/m3	2006/15/EC
	Further information: Indicative			
		OELV - 8 hrs (TWA)	20 ppm 72 mg/m3	IE OEL
	Further information: Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body			

**Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:**

Substance name	End Use	Exposure routes	Potential health effects	Value
acetone	Workers	Dermal	Long-term systemic effects	186 mg/kg
	Workers	Inhalation	Acute local effects	2420 mg/m3
	Workers	Inhalation	Long-term systemic effects	1210 mg/m3
ethyl acetate	Workers	Inhalation	Acute systemic effects	1468 mg/m3
	Workers	Inhalation	Acute local effects	1468 mg/m3
	Workers	Inhalation	Long-term systemic effects	734 mg/m3
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	Workers	Inhalation	Long-term systemic effects	2,035 mg/m3
butanone	Workers	Dermal	Long-term systemic effects	1161 mg/kg
	Workers	Inhalation	Long-term systemic effects	600 mg/kg
n-hexane	Workers	Dermal	Long-term systemic effects	13 mg/kg
	Workers	Inhalation	Long-term systemic effects	93 mg/m3

**SAFETY DATA SHEET**

according to Regulation (EC) No. 1907/2006

**Köraplast® SF**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	24.08.2022	100000017516	Date of first issue: 24.08.2022

**Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:**

Substance name	Environmental Compartment	Value
acetone	Marine water	1,06 mg/l
	Fresh water	10,6 mg/l
	Fresh water sediment	30,4 mg/l
	Marine sediment	3,04 mg/l
	Soil	0,112 mg/l
	Sewage treatment plant	29,5 mg/l
ethyl acetate	Fresh water	0,26 mg/l
	Intermittent use/release	1,65 mg/l
	Marine water	0,026 mg/l
	Fresh water sediment	1,25 mg/kg
	Marine sediment	0,125 mg/kg
	Soil	0,24 mg/kg
	Sewage treatment plant	650 mg/l

**8.2 Exposure controls****Engineering measures**

Please take care on national and local requirements.

**Personal protective equipment**

Eye protection : Tightly fitting safety goggles

Hand protection

Remarks : The glove material has to be impermeable and resistant to the product/the substance/the preparation.  
The exact break through time can be obtained from the protective glove producer and this has to be observed.  
The gloves need to be disposed after the penetration time and replaced by new ones.  
Apply skin protectant before working with gloves to avoid skin swellings and use a skin cleansing and skincare product after the work.

**For the permanent contact gloves made of the following materials are suitable:**

If longer exposure to the chemical preparation is necessary, a sturdy overglove against mechanical strain is recommended in combination with the Barrier 02-100 underglove from Ansell or other suppliers (penetration time: 480 min).

**For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**

Butyl rubber (minimum thickness: 0.7 mm; penetration time:



**SAFETY DATA SHEET**

according to Regulation (EC) No. 1907/2006

**Köraplast® SF**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	24.08.2022	100000017516	Date of first issue: 24.08.2022

---

15 min)

**As protection from splashes gloves made of the following materials are suitable:**

Nitril (minimum thickness 0.12 mm), Disposable gloves with long cuffs

After contact with the chemical preparation, take the disposable nitrile glove off immediately and put on a new disposable nitrile glove.

- |                          |   |  |
|--------------------------|---|--|
| Skin and body protection | : | Protective clothing  |
| Respiratory protection   | : | Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.<br>In case of brief exposure or low pollution (exceeding of TLV) use breathing filter apparatus.<br>In case of intensive or longer exposure use breathing apparatus that is independent of circulating air.<br>Ensure that suitable extractors are available on processing machines. |
| Protective measures      | : | Keep away from food, drink and animal feedingstuffs.<br>Instantly remove any soiled and impregnated garments.<br>Wash hands before breaks and immediately after handling the product.<br>Avoid contact with the eyes and skin.<br>Store protective clothing separately.  |

---

**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties**

- |                              |   |                   |
|------------------------------|---|-------------------|
| Physical state               | : | liquid            |
| Colour                       | : | colourless        |
| Odour                        | : | solvent-like      |
| Odour Threshold              | : | is not determined |
| Melting point/freezing point | : | is not determined |
| Boiling point/boiling range  | : | 56 °C             |
| Flash point                  | : | -17 °C            |
| Auto-ignition temperature    | : | is not determined |

**SAFETY DATA SHEET**

according to Regulation (EC) No. 1907/2006

**Köraplast® SF**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	24.08.2022	100000017516	Date of first issue: 24.08.2022

---

Decomposition temperature	:	Not applicable
pH	:	substance/mixture is non-polar/aprotic
Viscosity		
Viscosity, dynamic	:	2.700 mPa.s (20 °C)
Viscosity, kinematic	:	> 20,5 mm <sup>2</sup> /s (40 °C)
Solubility(ies)		
Water solubility	:	not miscible or difficult to mix
Partition coefficient: n-octanol/water	:	no data available
Vapour pressure	:	240 hPa (20 °C)
Density	:	0,86 g/cm <sup>3</sup> (20 °C)
Relative vapour density	:	is not determined

**9.2 Other information**

Explosives	:	Product is not explosive. However, formation of explosive vapour/air mixtures is possible.
Evaporation rate	:	is not determined

---

**SECTION 10: Stability and reactivity****10.1 Reactivity**

No further relevant information available.

**10.2 Chemical stability**

No decomposition if used according to the specifications.

**10.3 Possibility of hazardous reactions**

Hazardous reactions	:	Develops readily flammable vapours/fumes.
---------------------	---	---

**10.4 Conditions to avoid**

Conditions to avoid	:	No further relevant information available.
---------------------	---	--

**10.5 Incompatible materials**

Materials to avoid	:	No further relevant information available.
--------------------	---	--

**SAFETY DATA SHEET**

according to Regulation (EC) No. 1907/2006

**Köraplast® SF**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	24.08.2022	100000017516	Date of first issue: 24.08.2022

---

**10.6 Hazardous decomposition products**

No hazardous decomposition products are known.

---

**SECTION 11: Toxicological information****11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity****Product:**

Acute oral toxicity : Based on available data, the classification criteria are not met.

Acute inhalation toxicity : Based on available data, the classification criteria are not met.

Acute dermal toxicity : Based on available data, the classification criteria are not met.

**Components:****n-hexane:**

Acute dermal toxicity : LD50 Dermal (Rabbit): 3.000 mg/kg

**11.2 Information on other hazards****Endocrine disrupting properties****Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

---

**SECTION 12: Ecological information****12.1 Toxicity****Components:****n-hexane:**Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 2,1 - 2,98 mg/l  
Exposure time: 96 h  
Test Type: flow-through test**12.2 Persistence and degradability**

No data available

**SAFETY DATA SHEET**

according to Regulation (EC) No. 1907/2006

**Köraplast® SF**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	24.08.2022	100000017516	Date of first issue: 24.08.2022

---

**12.3 Bioaccumulative potential**

No data available

**12.4 Mobility in soil****Product:**

Mobility : Medium: Soil  
Remarks: Do not allow product to reach ground water, water bodies or sewage system.

**12.5 Results of PBT and vPvB assessment****Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

**12.6 Endocrine disrupting properties****Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

**12.7 Other adverse effects**

No data available

---

**SECTION 13: Disposal considerations****13.1 Waste treatment methods**

Product : Do not dispose of with domestic refuse.  
Do not dispose of waste into sewer.  
Hand over to disposers of hazardous waste.  
The generation of waste should be avoided or minimized wherever possible.  
Incinerate under controlled conditions in accordance with all local and national laws and regulations.  
Disposal must be made according to official regulations.

These EU waste code numbers are recommendations for waste accruing through the use of adhesives and sealants. Any waste produced from organic solvents or other dangerous substances (according GHS) listed under section 3 of this safety datasheet is itself classified as dangerous (\*).

**Waste accruing during application:**

**SAFETY DATA SHEET**

according to Regulation (EC) No. 1907/2006

**Köraplast® SF**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	24.08.2022	100000017516	Date of first issue: 24.08.2022

08 04 09\* waste adhesives and sealants containing organic solvents or other dangerous substances  
08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

**Waste accruing during cleaning:**

08 04 11\* adhesive and sealant sludges containing organic solvents or other dangerous substances  
08 04 12 adhesive and sealant sludges other than those mentioned in 08 04 11

**Waste packaging:**

15 01 01 paper and cardboard packaging  
15 01 02 plastic packaging  
15 01 04 metallic packaging  
15 01 10\* packaging containing residues of or contaminated by dangerous substances.

Contaminated packaging : Disposal must be made according to official regulations.

---

**SECTION 14: Transport information****14.1 UN number or ID number**

ADR : UN 1133  
RID : UN 1133  
IMDG : UN 1133  
IATA : UN 1133

**14.2 UN proper shipping name**

ADR : ADHESIVES  
RID : ADHESIVES  
IMDG : ADHESIVES  
IATA : Adhesives

**14.3 Transport hazard class(es)**

ADR : 3  
RID : 3  
IMDG : 3  
IATA : 3

**14.4 Packing group**

ADR  
Packing group : II

**SAFETY DATA SHEET**

according to Regulation (EC) No. 1907/2006

**Köraplast® SF**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	24.08.2022	100000017516	Date of first issue: 24.08.2022

Classification Code : F1  
Hazard Identification Number : 33  
Labels : 3  
Tunnel restriction code : (D/E)

**RID**

Packing group : II  
Classification Code : F1  
Hazard Identification Number : 33  
Labels : 3

**IMDG**

Packing group : II  
Labels : 3  
EmS Code : F-E, S-D

**IATA (Cargo)**

Packing instruction (cargo aircraft) : 364  
Packing instruction (LQ) : Y341  
Packing group : II  
Labels : Flammable Liquids

**IATA\_P (Passenger)**

Packing instruction (passenger aircraft) : 353  
Packing instruction (LQ) : Y341  
Packing group : II  
Labels : Flammable Liquids

**14.5 Environmental hazards****ADR**

Environmentally hazardous : no

**RID**

Environmentally hazardous : no

**IMDG**

Marine pollutant : no

**14.6 Special precautions for user**

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

**14.7 Maritime transport in bulk according to IMO instruments**

Not applicable for product as supplied.

---

**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

**SAFETY DATA SHEET**

according to Regulation (EC) No. 1907/2006

**Köraplast® SF**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	24.08.2022	100000017516	Date of first issue: 24.08.2022

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:  
Number on list 3

acetic acid

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

RoHS: 2011/65/EU, Restriction of Hazardous Substances : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EU) 2019/1148 on the marketing and use of explosives precursors

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point. : acetone (ANNEX II)

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P5c FLAMMABLE LIQUIDS

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content: 80,98 %, 696,4 g/l

**Other regulations:**

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

**The components of this product are reported in the following inventories:**

TCSI : On the inventory, or in compliance with the inventory

**SAFETY DATA SHEET**

according to Regulation (EC) No. 1907/2006

**Körplast® SF**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	24.08.2022	100000017516	Date of first issue: 24.08.2022

---

TSCA	:	All substances listed as active on the TSCA inventory
AIIC	:	On the inventory, or in compliance with the inventory
KECI	:	On the inventory, or in compliance with the inventory
IECSC	:	On the inventory, or in compliance with the inventory
REACH	:	On the inventory, or in compliance with the inventory

**15.2 Chemical safety assessment**

No Chemical Safety Assessment has been carried out for this mixture.

---

**SECTION 16: Other information****Full text of H-Statements**

H225	:	Highly flammable liquid and vapour.
H304	:	May be fatal if swallowed and enters airways.
H315	:	Causes skin irritation.
H319	:	Causes serious eye irritation.
H336	:	May cause drowsiness or dizziness.
H361f	:	Suspected of damaging fertility.
H373	:	May cause damage to organs through prolonged or repeated exposure.
H411	:	Toxic to aquatic life with long lasting effects.
EUH066	:	Repeated exposure may cause skin dryness or cracking.

**Full text of other abbreviations**

Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Eye Irrit.	:	Eye irritation
Flam. Liq.	:	Flammable liquids
Repr.	:	Reproductive toxicity
Skin Irrit.	:	Skin irritation
STOT RE	:	Specific target organ toxicity - repeated exposure
STOT SE	:	Specific target organ toxicity - single exposure
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2006/15/EC	:	Europe. Indicative occupational exposure limit values
2017/164/EU	:	Europe. Commission Directive 2017/164/EU establishing a fourth list of indicative occupational exposure limit values
IE OEL	:	Ireland. List of Chemical Agents and Occupational Exposure Limit Values - Schedule 1
2000/39/EC / TWA	:	Limit Value - eight hours



**SAFETY DATA SHEET**

according to Regulation (EC) No. 1907/2006

**Körplast® SF**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	24.08.2022	100000017516	Date of first issue: 24.08.2022

2000/39/EC / STEL	:	Short term exposure limit
2006/15/EC / TWA	:	Limit Value - eight hours
2017/164/EU / STEL	:	Short term exposure limit
2017/164/EU / TWA	:	Limit Value - eight hours
IE OEL / OELV - 8 hrs (TWA)	:	Occupational exposure limit value (8-hour reference period)
IE OEL / OELV - 15 min (STEL)	:	Occupational exposure limit value (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

**Further information**

Other information : This safety datasheet only contains information relating to safety and does not replace any product information or product specification.

Contact Point : Prepared by: Global Regulatory Department  
EU-MSDS@hbfuller.com

**Classification of the mixture:****Classification procedure:**

**SAFETY DATA SHEET**

according to Regulation (EC) No. 1907/2006

**Köraplast® SF**

Version	Revision Date:	SDS Number:	Date of last issue: - Date of first issue: 24.08.2022
1.0	24.08.2022	100000017516	
Flam. Liq. 2	H225	Based on product data or assessment	
Eye Irrit. 2	H319	Calculation method	
STOT SE 3	H336	Calculation method	
Aquatic Chronic 3	H412	Calculation method	

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

IE / EN