

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10.08.2022	10000016798	Date of first issue: 10.08.2022

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier Product name	:	H.B. Fuller® PRENOFIX 100 00
1.2 Relevant identified uses of th	ne s	substance or mixture and uses advised against
Use of the Sub- stance/Mixture	:	
Recommended restrictions on use	:	For industrial use only.
1.3 Details of the supplier of the	saf	ety data sheet
Company	:	H.B. Fuller, Isar-Rakoll, S.A.
Address	•	Estrada Nacional 13 PT-4486-851 Mindelo - Vila do Conde +351 229 288 200
E-mail address of person responsible for the SDS	:	EU-MSDS@hbfuller.com
1.4 Emergency telephone number	٩r	
		+44 1235 239 670 (24 hours)
		National Poisons Information Centre (NPIC): 01 809 2566

National Poisons Information Centre (NPIC): 01 809 2566 (24 hours)

## **SECTION 2: Hazards identification**

## **2.1 Classification of the substance or mixture**

Classification (REGULATION (EC) No 12 Flammable liquids, Category 2	<b>72/2008)</b> H225: Highly flammable liquid and vapour.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Reproductive toxicity, Category 2	H361d: Suspected of damaging the unborn child.
Specific target organ toxicity - repeated exposure, Category 2	H373: May cause damage to organs through pro- longed or repeated exposure.
Long-term (chronic) aquatic hazard, Cat- egory 2	H411: Toxic to aquatic life with long lasting effects.



|--|

## 2.2 Label elements

Labelling (REGULATION (E Hazard pictograms	No 1272/2008)	
Signal word	Danger	
Hazard statements	<ul> <li>H225 Highly flammable liquid and vapour.</li> <li>H315 Causes skin irritation.</li> <li>H319 Causes serious eye irritation.</li> <li>H361d Suspected of damaging the unborn child.</li> <li>H373 May cause damage to organs through prolonged or repeated exposure.</li> <li>H411 Toxic to aquatic life with long lasting effects.</li> </ul>	
Precautionary statements	<ul> <li>Prevention:</li> <li>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</li> <li>P260 Do not breathe mist or vapours.</li> <li>P273 Avoid release to the environment.</li> <li>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.</li> </ul>	tec-
	<b>Response:</b> P370 + P378 In case of fire: Use dry sand, dry chemical of alcohol-resistant foam to extinguish. P391 Collect spillage.	or
•	n <b>must be listed on the label:</b> is, isoalkanes, cyclics, <5% n-hexane	
Additional Labelling		
EUH208 Contains Ro	n. May produce an allergic reaction.	

EUH208 Contains Rosin, dodecane-1-thiol. May produce an allergic reaction.

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10.08.2022	10000016798	Date of first issue: 10.08.2022

## **SECTION 3: Composition/information on ingredients**

## 3.2 Mixtures

Components
------------

Components		Clossification	Concentration
Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n- hexane	64742-49-0 921-024-6 01-2119475514-35- 0000	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Aquatic Chronic 2; H411 Skin Irrit. 2; H315 STOT SE 3; H336 (Respiratory system)	>= 25 - < 30
ethyl acetate	141-78-6 205-500-4 607-022-00-5 01-2119475103-46- 0000	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system) EUH066	>= 10 - < 20
Hydrocarbons, C6-7	92128-66-0 295-763-1 01-2119486291-36- 0000	Flam. Liq. 2; H225 STOT SE 3; H336 (Central nervous system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411 EUH066	>= 10 - < 20
toluene	108-88-3 203-625-9 601-021-00-3 01-2119471310-51- 0000	Flam. Liq. 2; H225 Skin Irrit. 2; H315 Repr. 2; H361d STOT SE 3; H336 (Central nervous system) STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 10 - < 20
methyl acetate	79-20-9 201-185-2 607-021-00-X 01-2119459211-47- 0000	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system) EUH066	>= 1 - < 10
n-hexane	110-54-3 203-777-6	Flam. Liq. 2; H225 Skin Irrit. 2; H315	>= 0,25 - < 1



Version 1.0	Revision Date: 10.08.2022	SDS Number: 100000016798	Date of last issue: - Date of first issue: 10.08.202	2
		601-037-00-0 01-211948041 0000	2-44- Repr. 2; H361f STOT SE 3; H336 (Central nervous system) STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Chronic 2; H411 specific concentration limit STOT RE 2; H373 >= 5 %	
Rosin	I	8050-09-7 232-475-7 650-015-00-7 01-211948041 0000	Skin Sens. 1; H317 Aquatic Chronic 2; H411 8-32-	>= 0,25 - < 1
dodeo	cane-1-thiol	112-55-0 203-984-1 01-211949131 0000	Skin Corr. 1C; H314 Eye Dam. 1; H318 8-31- Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 0,0025 - < 0,025

For explanation of abbreviations see section 16.

## **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

General advice	:	If on clothes, remove clothes. Move the victim to fresh air. Show this safety data sheet to the doctor in attendance. Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
If inhaled	:	Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of unconsciousness bring patient into stable side position for transport.
In case of skin contact	:	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.
In case of eye contact	:	Flush eyes with water at least 15 minutes. Get medical atten- tion if eye irritation develops or persists.



Version 1.0	Revision Date: 10.08.2022		05 Number: 0000016798	Date of last issue: - Date of first issue: 10.08.2022
If swallowed		:	<ul> <li>If accidentally swallowed obtain immediate medical atten Rinse mouth with water.</li> <li>If conscious, drink plenty of water.</li> <li>Do NOT induce vomiting.</li> <li>If symptoms persist, call a physician.</li> </ul>	
	<b>mportant symptoms ar</b> known.	nd e	effects, both acu	te and delayed
4.3 Indica	tion of any immediate	mea	dical attention ar	nd special treatment needed
Treat	ment	:	No further releva	ant information available.
SECTION	1 5: Firefighting meas	sur	es	
5.1 Exting	uishing media			
Suital	ole extinguishing media	:		ng measures that are appropriate to local cir- I the surrounding environment.
Unsu media	itable extinguishing a	:	Water with a full water jet	
5 2 Specia	al hazards arising from	the	substance or m	ixture
-	fic hazards during fire-			ant information available.
5.3 Advice	e for firefighters			
Speci	al protective equipment efighters	:	No special prote	ctive measures against fire required.
Furth	er information	:	Fire residues an be disposed of in Collect contamir	re, wear self-contained breathing apparatus. d contaminated fire extinguishing water must n accordance with local regulations. nated fire extinguishing water separately. This charged into drains.

## **SECTION 6:** Accidental release measures

## 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions :	Remove all sources of ignition. Use personal protective equipment.
	Use breathing protection against the effects of



Version 1.0	Revision Date: 10.08.2022	SDS Number: 100000016798	Date of last issue: - Date of first issue: 10.08.2022
			erosol. sonnel to safe areas. uate ventilation.
6.2 Enviro	onmental precautions		
Envir	Environmental precautions :		should not be allowed to enter drains, water e soil. naterial from reaching sewage system, holes and contaminates rivers and lakes or drains inform thorities.
6.3 Metho	ods and material for co	ontainment and cle	eaning up
Meth	ods for cleaning up	acid binder, u Non-sparking Ensure adequ	inert absorbent material (e.g. sand, silica gel, niversal binder, sawdust). tools should be used. uate ventilation. very or disposal in suitable containers.

### 6.4 Reference to other sections

Refer to protective measures listed in sections 7 and 8., For disposal considerations see section 13.

tion 13.

Dispose of contaminated material as waste according to sec-

## **SECTION 7: Handling and storage**

### 7.1 Precautions for safe handling

Advice on safe handling	:	Avoid formation of dust and aerosols. Use only with adequate ventilation. Take note of emission threshold. Use solvent-proof equipment. Ensure that suitable extractors are available on processing machines. Handle with care. Keep eye wash bottle available on working place. Avoid release to the environment. Keep away from children.
Advice on protection against fire and explosion	:	Keep product and empty container away from heat and sources of ignition. Do not smoke. Take measures to prevent the build up of electrostatic charge. May form explosive mix- tures in air. Highly volatile, flammable constituents are re- leased during processing. In the event of fire and/or explosion do not breathe fumes. Keep breathing equipment ready. Have fire extinguishing equipment ready in case of nearby fire.



Version 1.0	Revision Date: 10.08.2022		DS Number: 00000016798	Date of last issue: - Date of first issue: 10.08.2022
7.2 Cond	litions for safe storage,	inc	luding any incom	patibilities
	uirements for storage is and containers	:	Keep dark, cool a	and dry. Store in cool place.
	her information on stor- conditions	:	ventilated place.	tightly closed in a dry, cool and well- Store in a cool place. Heat will increase y lead to the container exploding.
•	<b>ific end use(s)</b> cific use(s)	:	No further releva	nt information available.

## **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

### **Occupational Exposure Limits**

		•		-				
Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis				
		, ,	200					
ethyl acetate	141-78-6	OELV - 8 hrs	200 ppm	IE OEL				
		(TWA)	734 mg/m3					
		OELV - 15 min	400 ppm	IE OEL				
		(STEL)	1.468 mg/m3					
		STEL	400 ppm	2017/164/EU				
			1.468 mg/m3					
	Further inform	hation: Indicative						
		TWA	200 ppm	2017/164/EU				
			734 mg/m3					
	Further inform	hation: Indicative						
toluene	108-88-3	TWA	50 ppm	2006/15/EC				
			192 mg/m3					
	through the s							
		STEL	100 ppm	2006/15/EC				
			384 mg/m3					
	Further information: Indicative, Identifies the possibility of significant uptake							
	through the s							
		OELV - 8 hrs	50 ppm	IE OEL				
		(TWA)	192 mg/m3					
	Further inform	nation: Substances v	which have the capacity to pe	enetrate intact				
			ith it, and be absorbed into th					
		OELV - 15 min	100 ppm	IE OEL				
		(STEL)	384 mg/m3					
	Further information: Substances which have the capacity to penetrate intact							
			ith it, and be absorbed into th					
methyl acetate	79-20-9	OELV - 8 hrs	200 ppm	IE OEL				
		(TWA)	610 mg/m3					
		OELV - 15 min	250 ppm	IE OEL				
	1							



Versi 1.0	on Revision Da 10.08.2022				
	n-hexane	110-54-3	(STEL) TWA	760 mg/m3 20 ppm 72 mg/m3	2006/15/EC
		Further inform	nation: Indicative	· · ·	
			OELV - 8 hrs (TWA)	20 ppm 72 mg/m3	IE OEL
				which have the capacity to pe with it, and be absorbed into th	
(	dodecane-1-thiol	112-55-0	OELV - 8 hrs (TWA)	0,1 ppm	IE OEL
			of the respiratory tr	gents which following exposure act and lead to asthma, rhinitis	

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health ef- fects	Value
Hydrocarbons, C6- C7, n-alkanes, isoal- kanes, cyclics, <5% n-hexane	Workers	Inhalation	Long-term systemic effects	2,035 mg/m3
ethyl acetate	Workers	Inhalation	Acute systemic ef- fects	1468 mg/m3
	Workers	Inhalation	Acute local effects	1468 mg/m3
	Workers	Inhalation	Long-term systemic effects	734 mg/m3
toluene	Workers	Dermal	Long-term systemic effects	384 mg/kg
	Workers	Inhalation	Acute systemic ef- fects	384 mg/m3
	Workers	Inhalation	Acute local effects	384 mg/m3
	Workers	Inhalation	Long-term local ef- fects	192 mg/m3
	Workers	Inhalation	Long-term systemic effects	192 mg/m3
n-hexane	Workers	Dermal	Long-term systemic effects	13 mg/kg
	Workers	Inhalation	Long-term systemic effects	93 mg/m3

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment Value		
ethyl acetate	Fresh water	0,26 mg/l	
	Intermittent use/release	1,65 mg/l	
	Marine water	0,026 mg/l	
	Fresh water sediment	1,25 mg/kg	
	Marine sediment	0,125 mg/kg	
	Soil	0,24 mg/kg	
	Sewage treatment plant	650 mg/l	
toluene	Fresh water sediment	0,68 mg/l	



Version 1.0	Revision Date: 10.08.2022	SDS Number: 100000016798	Date of last issue: - Date of first issue: 10.0	08.2022
		Marine sedim	ient	0,68 mg/l
		Sewage treat	ment plant	13,61 mg/l
		Fresh water s	Fresh water sediment	
		Marine sedim	Marine sediment	
		Soil		2,89 mg/kg

#### 8.2 Exposure controls

#### **Engineering measures**

Please take care on national and local requirements.

#### Personal protective equipment

Eye protection : Tightly fitting safety goggles

Hand protection

Remarks

The glove material has to be impermeable and resistant to the product/the substance/the preparation.
The exact break through time can be obtained from the protective glove producer and this has to be observed.
The gloves need to be disposed after the penetration time and replaced by new ones.
Apply skin protectant before working with gloves to avoid skin swellings and use a skin cleansing and skincare product after the work.

# For the permanent contact gloves made of the following materials are suitable:

If longer exposure to the chemical preparation is necessary, a sturdy overglove against mechanical strain is recommended in combination with the Barrier 02-100 underglove from Ansell or other suppliers (penetration time: 480 min).

#### For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable: Butyl rubber (minimum thickness: 0.7 mm; penetration time: 15 min)

#### As protection from splashes gloves made of the following materials are suitable:

Nitril (minimum thickness 0.12 mm), Disposable gloves with long cuffs

After contact with the chemical preparation, take the disposable nitrile glove off immediately and put on a new disposable nitrile glove.



Version 1.0	Revision Date: 10.08.2022	SDS Number: 100000016798	Date of last issue: - Date of first issue: 10.08.2022
Skin a	and body protection	: Protective clot	hing
Respiratory protection		tilation is prov exposures are In case of brie use breathing In case of inte ratus that is in	ry protection unless adequate local exhaust ven- ided or exposure assessment demonstrates that a within recommended exposure guidelines. If exposure or low pollution (exceeding of TLV) filter apparatus. nsive or longer exposure use breathing appa- dependent of circulating air. uitable extractors are available on processing
Prote	ctive measures	Instantly remo Wash hands b the product. Avoid contact	om food, drink and animal feedingstuffs. we any soiled and impregnated garments. before breaks and immediately after handling with the eyes and skin. ve clothing separately.

## **SECTION 9: Physical and chemical properties**

## 9.1 Information on basic physical and chemical properties

Physical state	:	liquid
Colour	:	yellow
Odour	:	characteristic
Odour Threshold	:	is not determined
Melting point/freezing point	:	is not determined
Initial boiling point and boiling range	:	57 °C
Flash point	:	-26 °C
Flash point Auto-ignition temperature	:	
	:	
Auto-ignition temperature	:	is not determined
Auto-ignition temperature Decomposition temperature	::	is not determined Not applicable



Version 1.0	Revision Date: 10.08.2022	SDS Number: 100000016798	Date of last issue: - Date of first issue: 10.08.2022
Solubility(ies) Water solubility		: not miscible o	or difficult to mix
	ion coefficient: n- ol/water	: no data availa	able
Dens	ity	: 0,85 g/cm3	
Relat	ive vapour density	: is not determi	ned
9.2 Other	information		
Explo	sives		explosive. However, formation of explosive stures is possible.
Evap	oration rate	: is not determi	ned
			· · · · · · · · · · · · · · · · · · ·

## **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

No further relevant information available.

#### 10.2 Chemical stability

No decomposition if used according to the specifications.

10.3 Possibility of hazardous reactions						
Hazardous reactions	:	Develops readily flammable vapours/fumes.				
10.4 Conditions to avoid						
Conditions to avoid	:	No further relevant information available.				
10.5 Incompatible materials						

# Materials to avoid : No further relevant information available.

## 10.6 Hazardous decomposition products

No hazardous decomposition products are known.

### **SECTION 11: Toxicological information**

## 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

#### Product:

Acute oral toxicity : Based on available data, the classification criteria are not met.



Versio 1.0	on	Revision Date: 10.08.2022		DS Number: 00000016798	Date of last issue: - Date of first issue: 10.08.2022
A	Acute ii	nhalation toxicity	:	Based on availab	le data, the classification criteria are not met.
А	Acute c	lermal toxicity	:	Based on availab	le data, the classification criteria are not met.
<u>c</u>	Compo	onents:			
te	oluene	9:			
A	Acute c	oral toxicity	:	LD50 Oral (Rat):	5.580 mg/kg
Д	Acute ii	nhalation toxicity	:	LC50 (Rat): 12,5 Exposure time: 4	
n	nethyl	acetate:			
	-	nhalation toxicity	:	LC50 (Rat): 1600 Exposure time: 4 Test atmosphere	h
n	n-hexa	ne:			
	Acute dermal toxicity		:	LD50 Dermal (Ra	ubbit): 3.000 mg/kg
11.2 l	nform	ation on other hazar	ds		
E	Endocrine disrupting prope		ertie	s	
P	Produc	<u>:t:</u>			
Ą	lssess	ment	:	ered to have ende REACH Article 57	ixture does not contain components consid- ocrine disrupting properties according to 7(f) or Commission Delegated regulation or Commission Regulation (EU) 2018/605 at higher.

## **SECTION 12: Ecological information**

12.1 Toxicity	
Components:	
methyl acetate: Toxicity to fish	: LC50 (Brachydanio rerio (zebrafish)): 250 - 350 mg/l Exposure time: 96 h Test Type: static test
<b>n-hexane:</b> Toxicity to fish	<ul> <li>LC50 (Pimephales promelas (fathead minnow)): 2,1 - 2,98 mg/l</li> <li>Exposure time: 96 h</li> <li>Test Type: flow-through test</li> </ul>



Version	Revision Date: 10.08.2022	SDS Number:	Date of last issue: -
1.0		100000016798	Date of first issue: 10.08.2022

### Rosin:

Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 3,8 - 5,4 mg/l Exposure time: 48 h
		Test Type: static test

#### 12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

#### 12.4 Mobility in soil

#### Product:

Mobility

: Medium: Soil Remarks: Do not allow product to reach ground water, water bodies or sewage system.

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Endocrine disrupting properties

|--|

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

No data available

### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product

Do not dispose of with domestic refuse.
 Do not dispose of waste into sewer.
 Hand over to disposers of hazardous waste.
 The generation of waste should be avoided or minimized wherever possible.
 Incinerate under controlled conditions in accordance with all



Version 1.0	Revision Date: 10.08.2022	SDS Number: 100000016798	Date of last issue: - Date of first issue: 10.08.2022
			onal laws and regulations. It be made according to official regulations.
		waste accruir Any waste pro substances (a	ste code numbers are recommendations for ng through the use of adhesives and sealants. oduced from organic solvents or other dangerous according GHS) listed under section 3 of this eet is itself classified as dangerous (*).
		08 04 09* ganic solvent 08 04 10	ing during application: waste adhesives and sealants containing or- s or other dangerous substances waste adhesives and sealants other than ned in 08 04 09
		08 04 11* ganic solvent 08 04 12	ing during cleaning: adhesive and sealant sludges containing or- s or other dangerous substances adhesive and sealant sludges other than ned in 08 04 11
		Waste packa	aina:
		15 01 01	paper and cardboard packaging
		15 01 02	plastic packaging
		15 01 04	metallic packaging
		15 01 10* nated by dan	packaging containing residues of or contami- gerous substances.
Conta	aminated packaging		t be made according to official regulations.

## **SECTION 14: Transport information**

### 14.1 UN number or ID number

ADR	:	UN 1133
RID	:	UN 1133
IMDG	:	UN 1133
ΙΑΤΑ	:	UN 1133
14.2 UN proper shipping name		
ADR	:	ADHESIVES
RID	:	ADHESIVES
IMDG	:	ADHESIVES (Naphtha (petroleum), hydrotreated light, CYCLOHEXANE)
ΙΑΤΑ	:	Adhesives

14.3 Transport hazard class(es)



Version 1.0	Revision Date: 10.08.2022		OS Number: 0000016798	Date of last issue: - Date of first issue: 10.08.2022
ADR		:	3	
RID		:	3	
IMDG		:	3	
ΙΑΤΑ		:	3	
14.4 Packii	ng group			
Classif Hazaro Labels	g group fication Code d Identification Number I restriction code	:	III F1 30 3 (D/E)	
Classif	g group fication Code d Identification Number	:	III F1 30 3	
<b>IMDG</b> Packin Labels EmS C		:	III 3 F-E, S-D	
Packin aircraft Packin	g instruction (LQ)	:	366 Y344 III Flammable Liquid	ds
Packin	P (Passenger)	:		
	ig instruction (LQ)	:	Y344 III Flammable Liquid	ds
14.5 Environmental hazards				
<b>ADR</b> Enviro	nmentally hazardous	:	yes	
<b>RID</b> Enviro	nmentally hazardous	:	no	
IMDG	pollutant	:	yes	
	al precautions for use	r		

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10.08.2022	10000016798	Date of first issue: 10.08.2022

Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

### **SECTION 15: Regulatory information**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	: Conditions of restriction for the fol- lowing entries should be considered: Number on list 3
	formaldehyde (Number on list 72, 28)
	methanol (Number on list 69) xylenes acetic acid
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	: Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	: Not applicable
Regulation (EU) 2019/1021 on persistent organic pollu- tants (recast)	: Not applicable
RoHS: 2011/65/EU, Restriction of Hazardous Substances	: Not applicable
Regulation (EC) No 649/2012 of the European Parlia- ment and the Council concerning the export and import of dangerous chemicals	: Not applicable
REACH - List of substances subject to authorisation (Annex XIV)	: Not applicable
Seveso III: Directive 2012/18/EU of the Europe- P5c an Parliament and of the Council on the control of major-accident hazards involving dangerous substances.	FLAMMABLE LIQUIDS
E2	ENVIRONMENTAL HAZARDS
emissions (integrated )	of 24 November 2010 on industrial pollution prevention and control) punds (VOC) content: 80,50 %, 684,2 g/l



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10.08.2022	10000016798	Date of first issue: 10.08.2022

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 14,37 %

### Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

The components of this pro TSCA	odu :	ct are reported in the following inventories: All substances listed as active on the TSCA inventory
KECI	:	On the inventory, or in compliance with the inventory
IECSC	:	On the inventory, or in compliance with the inventory
REACH	:	On the inventory, or in compliance with the inventory

### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture.

## **SECTION 16: Other information**

#### Full text of H-Statements

H304       :         H314       :         H315       :         H317       :         H318       :         H319       :         H361d       :         H361f       :         H373       :	<ul> <li>Highly flammable liquid and vapour.</li> <li>May be fatal if swallowed and enters airways.</li> <li>Causes severe skin burns and eye damage.</li> <li>Causes skin irritation.</li> <li>May cause an allergic skin reaction.</li> <li>Causes serious eye damage.</li> <li>Causes serious eye damage.</li> <li>Causes serious eye irritation.</li> <li>May cause drowsiness or dizziness.</li> <li>Suspected of damaging the unborn child.</li> <li>Suspected of damaging fertility.</li> <li>May cause damage to organs through prolonged or repeated exposure.</li> <li>Very toxic to aquatic life.</li> <li>Very toxic to aquatic life with long lasting effects.</li> </ul>
H411 : H412 :	Toxic to aquatic life with long lasting effects. Harmful to aquatic life with long lasting effects.
EUH066 :	Repeated exposure may cause skin dryness or cracking.
	Repeated exposure may cause skill dryness of clacking.



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10.08.2022	10000016798	Date of first issue: 10.08.2022

### Full text of other abbreviations

Aquatic Acute	:	Short-term (acute) aquatic hazard
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Eye Dam.	:	Serious eye damage
Eye Irrit.	:	Eye irritation
Flam. Liq.	:	Flammable liquids
Repr.	:	Reproductive toxicity
Skin Corr.	:	Skin corrosion
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation
STOT RE	:	Specific target organ toxicity - repeated exposure
STOT SE	:	Specific target organ toxicity - single exposure
2006/15/EC	:	Europe. Indicative occupational exposure limit values
2017/164/EU	:	Europe. Commission Directive 2017/164/EU establishing a
		fourth list of indicative occupational exposure limit values
IE OEL	:	Ireland. List of Chemical Agents and Occupational Exposure
		Limit Values - Schedule 1
2006/15/EC / TWA	:	Limit Value - eight hours
2006/15/EC / STEL	:	Short term exposure limit
2017/164/EU / STEL	:	Short term exposure limit
2017/164/EU / TWA	:	Limit Value - eight hours
IE OEL / OELV - 8 hrs (TWA)	:	Occupational exposure limit value (8-hour reference period)
IE OEL / OELV - 15 min	:	Occupational exposure limit value (15-minute reference peri-
(STEL)		od)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA -European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIOC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quanti-



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10.08.2022	100000016798	Date of first issue: 10.08.2022

tative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

#### **Further information**

Other information	:		nly contains information relating to lace any product information or prod-
Contact Point	:	Prepared by: Global Regulatory Department EU-MSDS@hbfuller.com	
Classification of the mixture:			Classification procedure:
Flam. Liq. 2	H2	25	Based on product data or assessment
Skin Irrit. 2	H3	15	Calculation method
Eye Irrit. 2	H3	19	Calculation method
Repr. 2	H3	61d	Calculation method
STOT RE 2	H3	73	Calculation method
Aquatic Chronic 2	H4	11	Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

IE / EN