

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Umbugzement™ 500 M

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	17.05.2022	100000019974	Date of first issue: 17.05.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier****Product name** : Umbugzement™ 500 M**1.2 Relevant identified uses of the substance or mixture and uses advised against**Use of the Sub-
stance/Mixture : AdhesiveRecommended restrictions
on use : For industrial use only.**1.3 Details of the supplier of the safety data sheet**

Company : H.B. Fuller, Isar-Rakoll, S.A.

Address : Estrada Nacional 13
PT-4486-851 Mindelo - Vila do Conde
+351 229 288 200E-mail address of person
responsible for the SDS : EU-MSDS@hbfuller.com**1.4 Emergency telephone number**

Emergency telephone number : +44 1235 239 670 (24 hours)

National Poisons Information Centre (NPIC): 01 809 2566 (24 hours)

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****Classification (REGULATION (EC) No 1272/2008)**

Flammable liquids, Category 2 H225: Highly flammable liquid and vapour.

Skin irritation, Category 2 H315: Causes skin irritation.

Specific target organ toxicity - single ex-
posure, Category 3, Central nervous
system H336: May cause drowsiness or dizziness.Long-term (chronic) aquatic hazard, Cat-
egory 2 H411: Toxic to aquatic life with long lasting effects.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Umbugzement™ 500 M

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	17.05.2022	100000019974	Date of first issue: 17.05.2022

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements :

- H225 Highly flammable liquid and vapour.
- H315 Causes skin irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.

Precautionary statements :

Prevention:

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P233 Keep container tightly closed.
- P261 Avoid breathing mist or vapours.
- P273 Avoid release to the environment.

Response:

- P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
- P391 Collect spillage.

Hazardous components which must be listed on the label:

Naphtha (petroleum), hydrotreated light

Additional Labelling

EUH208 Contains Cymbopogon winterianus, ext.. May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No.	Classification	Concentration (% w/w)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Umbugzement™ 500 M

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	17.05.2022	100000019974	Date of first issue: 17.05.2022

	Registration number		
Naphtha (petroleum), hydrotreated light	64742-49-0 927-510-4 01-2119475515-33-0000	Flam. Liq. 2; H225 Skin Irrit. 2; H315 STOT SE 3; H336 (Central nervous system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 70 - < 90
ethanol	64-17-5 200-578-6 603-002-00-5 01-2119457610-43-0000	Flam. Liq. 2; H225 Eye Irrit. 2; H319	>= 1 - < 10
Cymbopogon winterianus, ext.	91771-61-8 294-954-7	Acute Tox. 4; H302 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Chronic 2; H411	>= 0,1 - < 0,25

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- | | |
|-------------------------|--|
| General advice | : If on clothes, remove clothes.
Move the victim to fresh air.
Show this safety data sheet to the doctor in attendance.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident. |
| If inhaled | : Remove person to fresh air. If signs/symptoms continue, get medical attention.
In case of unconsciousness bring patient into stable side position for transport. |
| In case of skin contact | : Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
If skin irritation persists, call a physician. |
| In case of eye contact | : Flush eyes with water at least 15 minutes. Get medical attention if eye irritation develops or persists. |
| If swallowed | : If accidentally swallowed obtain immediate medical attention.
Rinse mouth with water.
If conscious, drink plenty of water.
Do NOT induce vomiting. |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Umbugzement™ 500 M

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	17.05.2022	100000019974	Date of first issue: 17.05.2022

If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No further relevant information available.

SECTION 5: Firefighting measures**5.1 Extinguishing media**

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Water mist
Foam
Dry powder
Carbon dioxide (CO₂)

Unsuitable extinguishing media : Water with a full water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : No further relevant information available.

5.3 Advice for firefighters

Special protective equipment for firefighters : No special protective measures against fire required.

Further information : In the event of fire, wear self-contained breathing apparatus. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Personal precautions : Remove all sources of ignition.
Use personal protective equipment.
Use breathing protection against the effects of fumes/dust/aerosol.
Evacuate personnel to safe areas.
Ensure adequate ventilation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Umbugzement™ 500 M

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	17.05.2022	100000019974	Date of first issue: 17.05.2022

6.2 Environmental precautions

Environmental precautions : The product should not be allowed to enter drains, water courses or the soil.
Prevent the material from reaching sewage system, holes and cellars.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Non-sparking tools should be used.
Ensure adequate ventilation.
Send for recovery or disposal in suitable containers.
Dispose of contaminated material as waste according to section 13.

6.4 Reference to other sections

Refer to protective measures listed in sections 7 and 8., For disposal considerations see section 13.

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

Advice on safe handling : Avoid formation of dust and aerosols.
Use only with adequate ventilation.
Take note of emission threshold.
Use solvent-proof equipment.
Ensure that suitable extractors are available on processing machines.
Handle with care.
Keep eye wash bottle available on working place.
Avoid release to the environment.
Keep away from children.

Advice on protection against fire and explosion : Keep product and empty container away from heat and sources of ignition. Do not smoke. Take measures to prevent the build up of electrostatic charge. May form explosive mixtures in air. Highly volatile, flammable constituents are released during processing. In the event of fire and/or explosion do not breathe fumes. Keep breathing equipment ready. Have fire extinguishing equipment ready in case of nearby fire.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage : Keep dark, cool and dry. Store in cool place.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Umbugzement™ 500 M

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	17.05.2022	100000019974	Date of first issue: 17.05.2022

areas and containers

Further information on storage conditions : Keep containers tightly closed in a dry, cool and well-ventilated place. Store in a cool place. Heat will increase pressure and may lead to the container exploding.

7.3 Specific end use(s)

Specific use(s) : No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Rubber, natural	9006-04-6	OELV - 8 hrs (TWA)	6 mg/m ³	IE OEL
	Further information: Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit value should be used			
		OELV - 8 hrs (TWA) (process dust)	6 mg/m ³	IE OEL
	Further information: Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit value should be used			
		OELV - 8 hrs (TWA) (Fumes)	0,6 mg/m ³	IE OEL
	Further information: Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit value should be used			
		OELV - 8 hrs (TWA)	0,6 mg/m ³	IE OEL
	Further information: Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit value should be used			
		OELV - 8 hrs (TWA)	0,0001 mg/m ³ (inhalable allergenic proteins)	IE OEL
ethanol	64-17-5	OELV - 15 min (STEL)	1.000 ppm	IE OEL

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
ethanol	Workers	Inhalation	Long-term systemic effects	950 mg/m ³
	Workers	Inhalation	Acute local effects	1900 mg/m ³
	Workers	Dermal	Long-term systemic	343 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Umbugzement™ 500 M

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	17.05.2022	100000019974	Date of first issue: 17.05.2022

			effects	
--	--	--	---------	--

8.2 Exposure controls**Engineering measures**

Please take care on national and local requirements.

Personal protective equipment

Eye protection : Tightly fitting safety goggles

Hand protection

Remarks : The glove material has to be impermeable and resistant to the product/the substance/the preparation.
The exact break through time can be obtained from the protective glove producer and this has to be observed.
The gloves need to be disposed after the penetration time and replaced by new ones.
Apply skin protectant before working with gloves to avoid skin swellings and use a skin cleansing and skincare product after the work.

For the permanent contact gloves made of the following materials are suitable:

If longer exposure to the chemical preparation is necessary, a sturdy overglove against mechanical strain is recommended in combination with the Barrier 02-100 underglove from Ansell or other suppliers (penetration time: 480 min).

For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Butyl rubber (minimum thickness: 0.7 mm; penetration time: 15 min)

As protection from splashes gloves made of the following materials are suitable:

Nitril (minimum thickness 0.12 mm), Disposable gloves with long cuffs

After contact with the chemical preparation, take the disposable nitrile glove off immediately and put on a new disposable nitrile glove.

Skin and body protection : Protective clothing

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Umbugzement™ 500 M

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	17.05.2022	100000019974	Date of first issue: 17.05.2022

Respiratory protection	: Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. In case of brief exposure or low pollution (exceeding of TLV) use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air. Ensure that suitable extractors are available on processing machines.
Protective measures	: Keep away from food, drink and animal feedingstuffs. Instantly remove any soiled and impregnated garments. Wash hands before breaks and immediately after handling the product. Avoid contact with the eyes and skin. Store protective clothing separately.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

Physical state	: liquid
Colour	: beige
Odour	: characteristic
Odour Threshold	: is not determined
Melting point/freezing point	: is not determined
Flash point	: -4 °C
Auto-ignition temperature	: is not determined
Decomposition temperature	: not applicable
pH	: is not determined
Viscosity	
Viscosity, dynamic	: 110 mPa.s (20 °C)
Viscosity, kinematic	: > 20,5 mm ² /s (40 °C)
Solubility(ies)	
Water solubility	: not miscible or difficult to mix

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Umbugzement™ 500 M

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	17.05.2022	100000019974	Date of first issue: 17.05.2022

Partition coefficient: n-octanol/water : no data available

Density : 0,7 g/cm³ (20 °C)

Relative vapour density : is not determined

9.2 Other information

Explosives : Product is not explosive. However, formation of explosive vapour/air mixtures is possible.

Evaporation rate : is not determined

SECTION 10: Stability and reactivity**10.1 Reactivity**

No further relevant information available.

10.2 Chemical stability

No decomposition if used according to the specifications.

10.3 Possibility of hazardous reactions

Hazardous reactions : Develops readily flammable vapours/fumes.

10.4 Conditions to avoid

Conditions to avoid : No further relevant information available.

10.5 Incompatible materials

Materials to avoid : No further relevant information available.

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity****Product:**

Acute oral toxicity : Based on available data, the classification criteria are not met.

Acute inhalation toxicity : Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Umbugzement™ 500 M

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	17.05.2022	100000019974	Date of first issue: 17.05.2022

Acute dermal toxicity : Based on available data, the classification criteria are not met.

Components:**ethanol:**

Acute inhalation toxicity : LC50 (Rat): 1.500 mg/l
Exposure time: 4 h
Test atmosphere: vapour

11.2 Information on other hazards**Endocrine disrupting properties****Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information**12.1 Toxicity**

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil**Product:**

Mobility : Medium: Soil
Remarks: Do not allow product to reach ground water, water bodies or sewage system., Very toxic to aquatic organisms, Toxic effects on fish and plankton, Danger to drinking water if even extremely small quantities leak into soil.

12.5 Results of PBT and vPvB assessment**Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Umbugzement™ 500 M

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	17.05.2022	100000019974	Date of first issue: 17.05.2022

0.1% or higher.

12.6 Endocrine disrupting properties**Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

No data available

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

Product : Do not dispose of with domestic refuse.
Do not dispose of waste into sewer.
Hand over to disposers of hazardous waste.
The generation of waste should be avoided or minimized wherever possible.
Incinerate under controlled conditions in accordance with all local and national laws and regulations.
Disposal must be made according to official regulations.

These EU waste code numbers are recommendations for waste accruing through the use of adhesives and sealants. Any waste produced from organic solvents or other dangerous substances (according GHS) listed under section 3 of this safety datasheet is itself classified as dangerous (*).

Waste accruing during application:

08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances
08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

Waste accruing during cleaning:

08 04 11* adhesive and sealant sludges containing organic solvents or other dangerous substances
08 04 12 adhesive and sealant sludges other than those mentioned in 08 04 11

Waste packaging:

15 01 01 paper and cardboard packaging
15 01 02 plastic packaging

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Umbugzement™ 500 M

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	17.05.2022	100000019974	Date of first issue: 17.05.2022

15 01 04 metallic packaging
15 01 10* packaging containing residues of or contaminated by dangerous substances.

Contaminated packaging : Disposal must be made according to official regulations.

SECTION 14: Transport information**14.1 UN number or ID number**

ADR : UN 1133
RID : UN 1133
IMDG : UN 1133
IATA : UN 1133

14.2 UN proper shipping name

ADR : ADHESIVES
RID : ADHESIVES
IMDG : ADHESIVES
(HEPTANE)
IATA : Adhesives

14.3 Transport hazard class(es)

ADR : 3
RID : 3
IMDG : 3
IATA : 3

14.4 Packing group

ADR
Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : (D/E)

RID
Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

IMDG

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Umbugzement™ 500 M

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	17.05.2022	100000019974	Date of first issue: 17.05.2022

Packing group	:	III
Labels	:	3
EmS Code	:	F-E, S-D

IATA (Cargo)

Packing instruction (cargo aircraft)	:	366
Packing instruction (LQ)	:	Y344
Packing group	:	III
Labels	:	Flammable Liquids

IATA_P (Passenger)

Packing instruction (passenger aircraft)	:	355
Packing instruction (LQ)	:	Y344
Packing group	:	III
Labels	:	Flammable Liquids

14.5 Environmental hazards**ADR**

Environmentally hazardous	:	yes
---------------------------	---	-----

RID

Environmentally hazardous	:	yes
---------------------------	---	-----

IMDG

Marine pollutant	:	yes
------------------	---	-----

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	:	Conditions of restriction for the following entries should be considered: Number on list 3
--	---	--

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	:	not applicable
---	---	----------------

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	:	not applicable
---	---	----------------

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Umbugzement™ 500 M

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	17.05.2022	100000019974	Date of first issue: 17.05.2022

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : not applicable

RoHS: 2011/65/EU, Restriction of Hazardous Substances : not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : not applicable

REACH - List of substances subject to authorisation (Annex XIV) : not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. E2 ENVIRONMENTAL HAZARDS

P5c FLAMMABLE LIQUIDS

Volatile organic compounds :

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 87,30 %, 611,1 g/l

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

The components of this product are reported in the following inventories:

REACH : On the inventory, or in compliance with the inventory

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture.

SECTION 16: Other information**Full text of H-Statements**

H225	: Highly flammable liquid and vapour.
H302	: Harmful if swallowed.
H304	: May be fatal if swallowed and enters airways.
H315	: Causes skin irritation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Umbugzement™ 500 M

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	17.05.2022	100000019974	Date of first issue: 17.05.2022

H317	:	May cause an allergic skin reaction.
H318	:	Causes serious eye damage.
H319	:	Causes serious eye irritation.
H336	:	May cause drowsiness or dizziness.
H411	:	Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	:	Acute toxicity
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Eye Dam.	:	Serious eye damage
Eye Irrit.	:	Eye irritation
Flam. Liq.	:	Flammable liquids
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation
STOT SE	:	Specific target organ toxicity - single exposure
IE OEL	:	Ireland. List of Chemical Agents and Occupational Exposure Limit Values - Schedule 1
IE OEL / OELV - 8 hrs (TWA)	:	Occupational exposure limit value (8-hour reference period)
IE OEL / OELV - 15 min (STEL)	:	Occupational exposure limit value (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Umbugzement™ 500 M

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	17.05.2022	100000019974	Date of first issue: 17.05.2022

Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information : This safety datasheet only contains information relating to safety and does not replace any product information or product specification.

Contact Point : Prepared by: Global Regulatory Department
EU-MSDS@hbfuller.com

Classification of the mixture:

Flam. Liq. 2	H225
Skin Irrit. 2	H315
STOT SE 3	H336
Aquatic Chronic 2	H411

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

IE / EN