

Printing date 25.04.2023 Version number 1.07 Revision: 25.04.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: GP Cutting Colour colourless nature

· Article number: 743 040 03

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

Not suitable for use in homeworker (DIY) applications.

· Application of the substance / the mixture

Paint Lacquer

Restricted to professional users.

· Uses advised against cosmetic products

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Götz Service GmbH

Carl-Benz-Str. 1

DE-73095 Albershausen Tel.: +49 (0)7161 61020 Fax.: +49 (0)7161 6102990

Informing department: Product safety department.

e-mail: info@goetz-service.com

1.4 Emergency telephone number:

Giftnotruf Munich (24h) Tel.: +49 (0)89 19240

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

The product is not classified, according to the GB CLP regulation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008 Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- · Precautionary statements

P501 Dispose of contents / container in accordance with local / regional / national / international regulations.

Additional information:

Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.

Safety data sheet available on request.

- · 2.3 Other hazards If the product adheres to skin, irritation may occur when it dries.
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients			
· 3.2 Mixtures			
CAS: 7732-18-5 EINECS: 231-791-2	water, distilled, conductivity or of similar purity	50 – 100%	
	·	(Contd. on page 2)	

Printing date 25.04.2023 Version number 1.07 Revision: 25.04.2023

Trade name: GP Cutting Colour colourless nature

	(0	Contd. of page 1)
	acrylic polymere	10 – 25%
CAS: 107-98-2	1-methoxypropan-2-ol	2.5 – 10%
EINECS: 203-539-1	♠ Flam. Liq. 3, H226; ♠ STOT SE 3, H336	
Index number: 603-064-00-3	•	
Reg.nr.: 01-2119457435-35		

• **Description:** Mixture of the substances listed below with harmless additions.

· Dangerous components:		
CAS: 107-98-2	1-methoxypropan-2-ol	2.5 – 10%
EINECS: 203-539-1 Index number: 603-064-00-3 Reg.nr.: 01-2119457435-35	♠ Flam. Liq. 3, H226; ♠ STOT SE 3, H336	
CAS: 1336-21-6 EINECS: 215-647-6 Index number: 007-001-01-2	ammonia, aqueous solution Skin Corr. 1B, H314; Aquatic Acute 1, H400	< 0.25%

[·] Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information

Instantly remove any clothing soiled by the product.

Personal protection for the First Aider.

Take affected persons out of danger area and instruct to lie down.

Take off contaminated clothing and wash it before reuse.

Seek medical treatment.

· After inhalation

In case of unconsciousness bring patient into stable side position for transport.

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

· After skin contact

Instantly wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.

· After swallowing

If swallowed, rinse mouth with water (only if the person is conscious).

Seek medical treatment.

A person vomiting while lying on their back should be turned onto their side.

Never give anything by mouth to an unconscious person.

- · Information for doctor treat symptomatically
- · 4.2 Most important symptoms and effects, both acute and delayed Gastric or intestinal trouble
- Danger Danger of impaired breathing.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents

CO₂ extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

Dried up material is combustible.

Use fire extinguishing methods suitable to surrounding conditions.

- · For safety reasons unsuitable extinguishing agents Water with a full water jet.
- · 5.2 Special hazards arising from the substance or mixture

Can be released in case of fire

Products of incomplete combustion

Carbon monoxide and carbon dioxide

(Contd. on page 3)

Printing date 25.04.2023 Version number 1.07 Revision: 25.04.2023

Trade name: GP Cutting Colour colourless nature

(Contd. of page 2)

- 5.3 Advice for firefighters
- · Protective equipment: Put on breathing apparatus.
- · Additional information

Collect contaminated fire fighting water separately. It must not enter drains.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Bring persons out of danger.

Avoid contact with spilled material.

Avoid contact with the eyes and skin.

· 6.2 Environmental precautions:

Prevent from spreading (e.g. by damming-in or oil barriers).

Do not allow to enter drainage system, surface or ground water.

Do not allow to enter the ground/soil.

Inform respective authorities in case product reaches water or sewage system.

If material reaches soil inform authorities responsible for such cases.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Contain larger amounts and pump up into suitable containers.

Stop leak if you can do so without risk.

Dispose of the material collected according to regulations.

· 6.4 Reference to other sections

No dangerous materials are released.

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Do not eat, drink or smoke while working.

Store in cool, dry place in tightly closed containers.

Use solvent-proof equipment.

Ensure good ventilation/exhaustion at the workplace.

Avoid contact with the eyes and skin.

The usual precautionary measures should be adhered to general rules for handling chemicals.

Do not inhale gases / fumes / aerosols.

- · Information about protection against explosions and fires: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- ·Storage

· Requirements to be met by storerooms and containers:

Provide floor trough without outlet.

Prevent any penetration into the ground.

Store only in the original container.

Unsuitable material for container:

copper

· Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidising agents.

· Further information about storage conditions:

Keep container tightly sealed.

Store in a cool place. Heat will increase pressure and may lead to the container exploding.

Protect from frost.

This product is hygroscopic.

Store in a cool place.

· Recommended storage temperature: 5 - 30°C

(Contd. on page 4)

 Printing date 25.04.2023
 Version number 1.07
 Revision: 25.04.2023

Trade name: GP Cutting Colour colourless nature

· Storage class 10 (flammable liquids)

· 7.3 Specific end use(s) No further relevant information available.

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Additional information about design of technical systems: No further data; see item 7.

			uire monitoring at the workplace:	
	-methoxypropa			
			value: 560 mg/m³, 150 ppm	
		Long-term Sk	value: 375 mg/m³, 100 ppm	
IOELV (Eı	ropean Union)	Short-term	value: 568 mg/m³, 150 ppm	
			value: 375 mg/m³, 100 ppm	
		Skin		
STEL / TW	'A (ELV) (EU)		value: 568 mg/m³, 150 ppm	
		Long-term \ Skin	value: 375 mg/m³, 100 ppm	
1336-21-6	ammonia, aque		1	
ELV (Euro	pean Union)	Long-term	value: 14 mg/m³, 20 ppm	
STEL (Eur	opean Union)	Short-term	value: $28 (15 \text{min.}) \text{ mg/m}^3$	
DNELs	<u> </u>	l		
	-methoxypropa	n-2-ol		
Oral	short-term, syst		mg/kg bw/day (consumer)	
		00	no data available	
	long-term, syste	emic effects	33 mg/kg bw/day (consumer)	
Dermal	short-term, loc	al effects	mg/kg bw/day (consumer) no data available	
			mg/kg bw/day (worker) no data available	
	short-term, syst	temic effects	mg/kg bw/day (consumer) no data available	
			mg/kg bw/day (worker) no data available	
	long-term, loca	ıl effects	mg/kg bw/day (worker) no data available	
	long-term, syste	emic effects	78 mg/kg bw/day (consumer)	
			183 mg/kg bw/day (worker)	
Inhalative	short-term, loca	al effects	553.5 mg/m³ (worker)	
	short-term, syst	temic effects	mg/m³ (consumer)	
			553.5 mg/m³ (worker)	
	long-term, loca	ıl effects	mg/m³ (consumer) no data available	
			mg/m³ (worker) no data available	
	long-term, syste	emic effects	43.9 mg/m³ (consumer)	
	_	-	369 mg/m³ (worker)	
1336-21-6	ammonia, aque	eous solution	1	
Oral	short-term, syst	temic effects	6.8 mg/kg bw/day (consumer)	
	long-term, syste	emic effects	6.8 mg/kg bw/day (consumer)	
Dermal	short-term, syst	temic effects	68 mg/kg bw/day (consumer)	

Printing date 25.04.2023 Version number 1.07 Revision: 25.04.2023

Trade name: GP Cutting Colour colourless nature

			(Contd. of pag
		6.8 mg/kg bw/day (worker)	
	long-term, systemic effects	68 mg/kg bw/day (consumer)	
		6.8 mg/kg bw/day (worker)	
Inhalative	short-term, local effects	7.2 mg/m³ (consumer)	
		36 mg/m³ (worker)	
	short-term, systemic effects	23.8 mg/m³ (consumer)	
		47.6 mg/m³ (worker)	
	long-term, local effects	2.8 mg/m³ (consumer)	
		14 mg/m³ (worker)	
	long-term, systemic effects	23.8 mg/m³ (consumer)	
		47.6 mg/m³ (worker)	

	TILES		
	107-98-2 1-methoxypropan-2-ol		
PNEC (Predicted No Effect Concentration) 100 mg/l (sewage treatment plant)		100 mg/l (sewage treatment plant)	
		1 mg/l (marine water)	
		10 mg/l (fresh water)	
		100 mg/l (intermittent release)	
	PNEC (Predicted No Effect Concentration)	4.59 mg/kg (soil (dry matter))	
		5.2 mg/kg (marine sediment (dry matter))	
		52.3 mg/kg (fresh water sediment (dry matter))	
	1336-21-6 ammonia, aqueous solution		
	PNEC (Predicted No Effect Concentration)	0.00011 mg/l (marine water)	
		0.0011 mg/l (fresh water)	

· Additional information:

The lists that were valid during the compilation were used as basis.

Note: Information about recommended monitoring procedures can be obtained from the relevant agency(ies)/institute(s): for the United Kingdom: UK Health and Safety Executive (HSE)

0.0068 mg/l (intermittent release)

· 8.2 Exposure controls

· Personal protective equipment

General protective and hygienic measures

The usual precautionary measures should be adhered to general rules for handling chemicals.

Wash hands during breaks and at the end of the work.

Do not eat, drink or smoke while working.

Avoid contact with the eyes and skin.

Do not inhale gases / fumes / aerosols.

Avoid close or long term contact with the skin.

· Breathing equipment: Filter A/P2.

· Protection of hands:

Protective gloves.

Only use chemical-protective gloves with CE-labelling of category III.

Check protective gloves prior to each use for their proper condition.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

After use of gloves apply skin-cleaning agents and skin cosmetics.

Protective gloves should be replaced at first signs of wear.

· Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: >0,5 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 6)

Printing date 25.04.2023 Version number 1.07 Revision: 25.04.2023

Trade name: GP Cutting Colour colourless nature

(Contd. of page 5)

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · As protection from splashes gloves made of the following materials are suitable: Nitrile rubber, NBR
- Not suitable are gloves made of the following materials:

Strong gloves Leather gloves

- · Eye protection: Safety glasses
- · Body protection: Protective work clothing.
- · Limitation and supervision of exposure into the environment

Do not allow to enter drainage system, surface or ground water.

Do not allow to enter the ground/soil.

Prevent from spreading (e.g. by damming-in or oil barriers).

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and ch General Information	icimicai properaco	
Appearance:		
Form:	Fluid	
Colour:	White	
Odour:	Ether-like	
Odour threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/freezing point:	Not determined.	
Initial boiling point and boiling range:	: 100 °C	
0.0	(water)	
Flash point:	Not determined.	
Ignition temperature:	287 °C	
1	Not determined.	
Decomposition temperature:	Not determined.	
Explosive properties:	Not determined.	
	Product is not explosive.	
Critical values for explosion:		
Lower:	2.3 Vol %	
Upper:	Not determined.	
Vapour pressure at 20 °C:	23.4 hPa	
	(water)	
Density at 20 °C	1.03 g/cm^3	
Relative density	Not determined.	
Vapour density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Fully miscible	
Partition coefficient: n-octanol/water:	See section 12	
Viscosity:		
dynamic:	Not determined.	
kinematic at 20 °C:	15 s (DIN 53211/4)	
Solvent content:		
Organic solvents:		
ЙОС (EU):	103.7 g/l	

Printing date 25.04.2023 Version number 1.07 Revision: 25.04.2023

Trade name: GP Cutting Colour colourless nature

		(Contd. of page 6)
VOC (%):	10.1 %	
· Water:	55.1 %	
· Solids content:	34.8 %	
· 9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

Protect from frost.

Protect from heat and direct sunlight.

· 10.3 Possibility of hazardous reactions

Reacts with acids, alkalis and oxidizing agents

Reacts with acid chlorides

- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials:

oxidizing agents

acids

salts

· 10.6 Hazardous decomposition products:

No hazardous decomposition products if stored and handled as prescribed/indicated.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity No toxicological test data are available for the whole product.
- · LD/LC50 values that are relevant for classification:

Based on available data, the classification criteria are not met.

*5vapour

107-98-2 1	107-98-2 1-methoxypropan-2-ol		
Oral	LD ₅₀ Acute toxicity:	4,016 mg/kg (rat)	
Dermal	LD_{50} Acute toxicity, dermal:	> 2,000 mg/kg (canine) Repeated exposure to the skin may cause resorption of harmful doses.	
Inhalative	LC_{50} (4 h) Acute toxicity, inhalative:	> 25.8 mg/l (rat) (6h)*5	
1336-21-6 ammonia, aqueous solution			
Oral	LD ₅₀ Acute toxicity:	> 2,000 mg/kg	
Dermal	LD ₅₀ Acute toxicity, dermal:	> 2,000 mg/kg	

- · Primary irritant effect:
- Skin corrosion/irritation

Irritation may occur.

If the product adheres to skin, irritation may occur when it dries.

The product has not been tested. The statement has been derived from the properties of the individual components.

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

· Serious eye damage/irritation

Irritation may occur.

The product has not been tested. The statement has been derived from the properties of the individual components.

107-98-2 1-methoxypropan-2-ol			
	Irritation of eyes	Serious eye damage/irritation:	pos. (canine)
			(Contd. on page 8)

(Contd. of page 7)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.04.2023 Version number 1.07 Revision: 25.04.2023

Trade name: GP Cutting Colour colourless nature

· Respiratory or skin sensitisation

Sensitization possible by skin contact.

May produce an allergic reaction.

The product has not been tested. The statement has been derived from the properties of the individual components.

107-98-2 1-methoxypropan-2-ol

Sensitization | Skin sensitisation: | neg. (guinea pig) (OECD Guideline 406)

- · Additional toxicological information: Danger by skin resorption.
- · Acute effects (acute toxicity, irritation and corrosivity) May cause respiratory irritation.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

No toxicological test data are available for the whole product.

107-98-2 1-methoxypropan-2-ol

Ames test (bacteria, not defined)

- · Developmental toxicity (teratogenicity) No data available.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure May cause respiratory irritation.
- · STOT-repeated exposure

Based on available data, the classification criteria are not met.

The available information is not sufficient for evaluation.

· Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:
107-98-2 1-mathoxynronau-2-ol

10/-90-2 1	-meinoxyp	ropun-2-oi

 $EC_{5\sigma}$ Bacterial toxicity(respiration inhibition > 1,000 mg/l (activated sludge) $EC_{5\sigma}$ Bacterial toxicity > 1,000 mg/l (Pseudomonas putida)

(7 d)

 $LC_{5\sigma}$ Fish toxicity (static) [6,812 mg/l (ide (Leuciscus idus))

(96 h)

≥ 1,000 mg/l (rainbow trout (Oncorhynchus mykiss)) (OECD

Guideline 203)

(96 h)

20,800 mg/l (fathead minnow (Pimephales promelas)) (OECD

Guideline 203)

(96 h)

 EC_{so} Toxicity for algae (static) | > 1,000 mg/l (green algae (Selenastrum capricornutum))

(7d)

 ErC_{50} -Toxicity for algae (growth inhibition) |> 1,

> 1,000 mg/l (Pseudokirchneriella subcapitata) (OECD

Guideline 201)

(7d)

 $LC_{5\sigma}$ Toxicity for daphnia (static) 21,100-25,900 mg/l (daphnia (Daphnia magna)) (OECD

Guideline 202)

(48 h)

· 12.2 Persistence and degradability No data on the mixture is available.

· Degree of elimination:

107-98-2 1-methoxypropan-2-ol

Biodegradability 96 % (28 days) (OECD 301 E)

Behaviour in environmental systems:

Water:

(Contd. on page 9)

Printing date 25.04.2023 Version number 1.07 Revision: 25.04.2023

Trade name: GP Cutting Colour colourless nature

(Contd. of page 8)

Fully miscible

· 12.3 Bioaccumulative potential No further relevant information available.

· Partition coefficient, n-octanol/water (log Pow):				
107-98-2	1-methoxypropan-2-ol	0,37		
2634-33-5	1,2-benzisothiazol-3(2H)-one	0,7 (OECD 117)		

Bioconcentration factor (BCF):

107-98-2 1-methoxypropan-2-ol

Bioconcentration factor (BCF): | < 100|

· 12.4 Mobility in soil No further relevant information available.

· 12.40.23.1 Partition coefficient, soil organic carbon/water (log Koc):

107-98-2 | 1-methoxypropan-2-ol | 0,2 - 1,0

- · Additional ecological information:
- · According to recipe contains the following heavy metals and compounds according to EC guideline NO. 76/464 EC:

Contains no adsorbable organically bound halogens (AOX)

General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water.

Avoid transfer into the environment.

Do not allow product to reach ground water, water bodies or sewage system.

· 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Disposal must be made according to official regulations.

None disposal into waste water.

· Waste disposal key number:

For disposal within the EC, the appropriate code according to the European Waste Catalogue (EWC) should be used.

- · Uncleaned packagings:
- · Recommendation:

Disposal must be made according to official regulations.

Packagings that cannot be cleaned are to be disposed of in the same manner as the product.

· Recommended cleaning agent: Water, if necessary with cleaning agent.

· 14.1 UN-Number		
· ADR, ADN, IMDG, IATA	Void	
· 14.2 UN proper shipping name		
· ADR, ADN, IMDG, IAŤA	Void	
· 14.3 Transport hazard class(es)		
· ADR, ADN, IMDG, IATA		
Class	Void	
· 14.4 Packing group		
· ADR, IMDĞ, İATA	Void	
· 14.5 Environmental hazards:		
· Marine pollutant:	No	

Printing date 25.04.2023 Version number 1.07 Revision: 25.04.2023

Trade name: GP Cutting Colour colourless nature

		(Contd. of page 9
· 14.6 Special precautions for user	Not applicable.	
· 14.7 Transport in bulk according to Ann Marpol and the IBC Code	nex II of Not applicable.	
· Transport/Additional information:		
· ADR · Excepted quantities (EQ)	NOT SUBJECT TO ADR	
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	- Code: -	
· UN "Model Regulation":	Void	

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Labelling according to Regulation (EC) No 1272/2008 Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · National regulations
- · Information about limitation of use:

Employment restrictions concerning pregnant and lactating women must be observed.

· Technical instructions (air):

Class	Share in %
Wasser	50 – 100
III	≤0.2
NK	10 - 25

- · Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · Other regulations, limitations and prohibitive regulations

TRGS 400 "Risk assessment for activities involving hazardous substances"

TRGS 500: "precautions: minimum standards"

TRGS 600 "Substitution"

TRGS 510 "Storage of hazardous substances in non-stationary containers"

Directive 2012/18/EÜ

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.

H314 Causes severe skin burns and eye damage.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

- · Department issuing data specification sheet: Laboratory
- · Contact:

(Contd. on page 11)

Printing date 25.04.2023 Version number 1.07 Revision: 25.04.2023

Trade name: GP Cutting Colour colourless nature

(Contd. of page 10)

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

bw: bodyweight

Langz., Langzeit: chronical exposure,

akut: acute (exposure) lokal: local effects

system., systemisch: systemic effects PNEC (Predicted No-EffectConcentration)

LC₅₀: lethal concentration for 50 percent of the animals or plants used for testing

LD₅₀: lethal dose for 50 percent of the animals used for testing

LDo: lethal concentration for 0 percent

LDo: lethal dose for 0 percent

nb / n.b.: not determined

gamete mutagenic. : gamete/germ cell mutagenicity

carcinogen.: carcinogeniticity

theoret. $O_{\mathcal{Z}}$ Bedarf: theoretical oxigen demand

AOX: adsorbable organically bound halogens

TRGS: technische Regeln für Gefahrstoffe (technical rules for dealing with dangerous substances)

Merkblatt BG-Chemie: datasheet of the "Berufsgenossenschaft Rohstoffe und chemische Industrie" (former: "Berufgenossenschaft

Chemie") (German insurance in case of accidents at work)

Langz., Langzeit: Long-term exposure

akut: Acute / short-term exposure

systemisch: systemic

lokal: local

n.a.: not applicable

(derived fr. data f.similar substances, intern.rep.) = derived from data from tests with similar substances, internal reports, not published

Vert.koeff.Bod./Wass = Partition Coefficient soil / water

n.v.: no data available

Susp.: suspension

H: the product is skin-resorbing Algentoxizität: toxicity for algae Bakterientoxizität: toxicity for bacteria Daphnientoxizität: toxicity for Daphnia Fischtoxizität: toxicity for fishes

biologische Abbaubarkeit: Biodegradation

DOC: dissolved organic carbon

Halbwertszeit: half-life

h: hour(s)

d: day(s)

w: week(s)

m: montht(s)

v. vear(s)

DIN: Norm des Deutschen Instituts für Normung = standard of the German Institute for Standardization

EN: Europäische Norm = standard of the European Committee for Standardization (CEN)

OECD: ÔECD Test Guideline

pos. : positive neg. : negative

inh., inhal. : inhalative

NOEC (No Observed Effect Concentration),

NOEL (No Observed Effect Level),

NOAEL (No Observed Adverse Effect Level): denotes the level of exposure of an organism at which there is no effect in the exposed population.

NOELR (No-Observed-Effect-Loading Rate)

ATE (Acute Toxicity Estimates)

Flam. Liq. 3: Flammable liquids – Category 3

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

· Sources http://www.dguv.de/ifa/en/gestis/stoffdb/index.jsp

* * Data compared to the previous version altered.